

¹*D.Hemanand
²C.Ambika
 Bhuvaneshwari
³S.Savitha
⁴M.Jothi
⁵R. Senthil Rama

Optimizing Energy-Efficient Communication Protocols for IoT Devices in Smart Cities Using Narrowband IoT and LTE-M Technology



Abstract: In the context of optimizing energy-efficient communication protocols for IoT devices in smart cities, this research addresses the pressing need for sustainable and reliable solutions. The research provides a comprehensive understanding of the strategies that contribute to minimizing energy consumption in smart city IoT deployments, with a specific focus on Narrowband IoT (NB-IoT) technology. Employing a structured framework and an integrated system architecture, incorporating LTE-M technology and an application server, the research leverages various optimization strategies. These include Adaptive Power Control, Duty Cycling, Data Aggregation, Protocol Optimization, and Network Topology Optimization. Methodologically, the study adopts a quantitative approach, utilizing metrics such as duty cycle percentages and energy consumption reductions. Data is collected through simulations and experiments, and the analysis involves assessing the impact of each optimization strategy on energy efficiency. Key findings demonstrate significant reductions in energy consumption, ranging from 15% to 25%, depending on the specific strategy employed. Adaptive Power Control and Network Topology Optimization emerge as particularly effective approaches. The implications of these findings underscore the importance of adopting tailored optimization strategies in smart city IoT deployments to achieve both energy efficiency and reliability. The study discusses the broader significance of these results and acknowledges potential limitations, paving the way for future research endeavors in the realm of sustainable and resource-conserving smart cities.

Keywords: Wireless Sensor Networks, Long-range Communication, Protocol Optimization, Narrowband Communication, IoT Infrastructure.

I. INTRODUCTION

The emergence of smart cities heralds a new era of urban living, where technological advancements play a pivotal role in enhancing efficiency, sustainability, and quality of life. Central to this vision are Internet of Things (IoT) devices, which enable seamless connectivity and data exchange between various elements of urban infrastructure. In particular, Narrowband IoT (NB-IoT) has emerged as a promising communication technology, offering low-power, wide-area coverage suitable for smart city deployments [1]. The proliferation of IoT devices in smart cities brings forth a myriad of opportunities, ranging from optimizing energy consumption to improving public safety and transportation systems. However, to fully realize these benefits, it is imperative to develop energy-efficient communication protocols tailored to the unique requirements of urban environments. Such protocols must strike a delicate balance between reliable data transmission and minimal energy consumption, ensuring the long-term sustainability and scalability of IoT deployments [2]. This research paper aims to explore and optimize energy-efficient communication protocols for IoT devices in smart cities using NB-IoT technology. By leveraging NB-IoT's low-power capabilities and wide coverage area, we seek to develop protocols that minimize energy consumption while maximizing data transmission reliability.

This endeavor encompasses a multidisciplinary approach, drawing insights from telecommunications, urban planning, and sustainability studies. The significance of this research lies in its potential to drive transformative changes in urban infrastructure, enabling cities to become smarter, more sustainable, and more resilient to future challenges [3]. By optimizing energy-efficient communication protocols, we can unlock new possibilities for IoT applications in areas such as environmental monitoring, traffic management, and public services delivery. Moreover, the outcomes of this research have far-reaching implications, extending beyond smart cities to encompass broader IoT deployments in various domains [4]. In conclusion, this research paper sets out to

¹Professor, Department of Computer Science and Engineering, S.A. Engineering College (Autonomous), Thiruverkadu, Chennai-600077, Tamil Nadu, India. Email: d.hemanand@gmail.com*

²Assistant Professor, Department of Electronics and Communication Engineering, Vel Tech Rangarajan Dr.Sagunthala R&D Institute of Science and Technology, Avadi-600062, Chennai, Tamil Nadu, India.

Email: ambikabhuvaneshwari@veltech.edu.in

³Assistant Professor, Department of computer science and Engineering, P.S.R.Engineering College ,Sivakasi, Tamil Nadu 626140 Email:savithamecse@gmail.com

⁴Assistant Professor, Department of Computer Science and Business Systems , PSNA College of Engineering and Technology , Dindigul-624622, Tamil Nadu ,India.Email:jothiraj56@gmail.com

⁵Associate Professor, Department of Electrical and Electronics and Communication Engineering, DMI College Engineering, Chennai, Tamil Nadu, India. Email: ramaherald@gmail.com

address the critical need for energy-efficient communication protocols for IoT devices in smart cities using NB-IoT technology. Through collaborative efforts and interdisciplinary approaches, we aim to pave the way toward a more sustainable and connected urban future where technology serves as a catalyst for positive change [5]. The objectives of the proposed work are:

- Develop a structured framework for optimizing communication protocols within IoT systems, specifically tailored for smart city deployments.
- Implement the proposed system architecture integrating LTE-M technology and an application server, emphasizing the use of NB-IoT for energy-efficient communication.
- Explore and leverage the unique features of NB-IoT technology to achieve energy savings in various smart city applications, such as smart metering and environmental monitoring.
- Apply duty cycling, data aggregation, adaptive transmission power control, and protocol optimization to enhance energy efficiency in IoT communication, with a focus on NB-IoT networks.
- Quantify the percentage reduction in energy consumption and validate the effectiveness of the proposed optimization strategies through simulations or real-world experiments.

2. LITERATURE REVIEW

Across the spectrum, various studies delve into optimizing NB-IoT for efficient communication protocols, resource management, and energy consumption. The efforts highlight the importance of efficient communication protocols for tasks like energy monitoring and management, offering promising avenues for sustainable urban development. However, challenges persist in scalability and interoperability, particularly with legacy systems. Other papers conduct comprehensive analyses of NB-IoT's resource management, energy efficiency, and reliability optimization. They provide valuable insights into performance metrics, challenges, and opportunities for enhancing network efficiency [6]. Yet, there are hurdles to overcome, including spectrum efficiency, coverage optimization, and interference mitigation, which require innovative solutions. Surveys and reviews offer a broad overview of NB-IoT's architecture, applications, and challenges, paving the way for informed decision-making in smart city deployments [7]. While these studies shed light on NB-IoT's potential, they also underscore the need for practical implementations and real-world deployment experiences to validate theoretical findings. Innovative proposals, such as hybrid protocols and energy-efficient scheduling techniques, demonstrate ongoing efforts to address NB-IoT's limitations and optimize its performance [8]. However, the lack of experimental validation and scalability analysis poses challenges in assessing the real-world efficacy of these solutions. Overall, the literature provides an understanding of NB-IoT's role in shaping the future of smart cities while also highlighting the need for continued research and development to overcome existing challenges and maximize its potential [9].

Some studies have homed in on specific applications of NB-IoT, such as its optimization for smart meter networks or energy-efficient solutions within urban environments. These investigations underscore the critical role of efficient communication protocols in tasks like monitoring and managing energy usage, offering promising avenues for sustainable city development. However, challenges persist, particularly in scaling up NB-IoT systems and ensuring they can seamlessly integrate with existing infrastructure [10]. Other research endeavors have undertaken comprehensive analyses of NB-IoT's resource management, energy efficiency, and reliability. By exploring performance metrics and identifying challenges, these studies provide valuable insights into how NB-IoT networks can be enhanced [11]. Yet, obstacles remain, including the need to improve spectrum efficiency, optimize coverage, and mitigate interference, all of which demand innovative solutions. Surveys and reviews within the literature offer a broader perspective on NB-IoT, covering its architecture, applications, and associated challenges [12]. These comprehensive overviews are instrumental in guiding decision-making processes related to deploying NB-IoT in smart city initiatives. Nonetheless, they also emphasize the importance of validating theoretical findings through practical implementations and real-world deployments [13].

The research in [14] addresses the vulnerability of IoT systems to cyberattacks by introducing a novel security architecture, VBQ-Net, utilizing Vector Space Bag of Words and Boosted Variance Quantization Neural Networks, along with the Multi-Hunting Reptile Search Optimization algorithm, to enhance intrusion detection and provide a more effective defense mechanism against cyber threats on IoT networks. The research in [15-18] proposes a security protocol for the IoT platform within Mobile Ad Hoc Networks (MANET), integrating three enhanced algorithms for an optimized key management scheme under a chaotic map, resulting in superior performance, particularly demonstrated by the Adaptive Basic Reproduction Rate-based

Coronavirus Herd Immunity Optimizer (ABRR-CHIO), in terms of statistical analysis, convergence analysis, and communication overhead. Innovative proposals, such as hybrid protocols and energy-efficient scheduling techniques, exemplify ongoing efforts to address the limitations of NB-IoT and optimize its performance further. However, the effectiveness of these solutions still requires validation through experimental testing and scalability analysis. In sum, the literature provides a nuanced understanding of NB-IoT's potential role in shaping the future of smart cities yet underscores the continued need for research and development to overcome existing challenges and fully maximize its benefits.

III. PROPOSED WORK




Fig.1. Framework of energy efficient communication in IoT

Optimizing Energy-Efficient Communication Protocols involves refining how devices in a smart city communicate to minimize energy usage. Similar to finding efficient communication methods for friends during a game, this process ensures devices exchange information with minimal energy consumption. Figure 1 provides a structured approach for optimizing communication processes in Internet of Things (IoT) systems. This framework outlines methodologies, strategies, and best practices for designing, implementing, and managing communication protocols in IoT deployments to minimize energy consumption while maintaining reliable communication. In a smart city, various devices like sensors, meters, and cameras are interconnected to gather and share data for better city management. These devices play roles like monitoring traffic flow, detecting environmental changes, or managing energy usage. Optimizing communication protocols for IoT devices in smart cities ensures these devices communicate efficiently, saving energy and allowing for quick and accurate information exchange.




Fig.2. Proposed System Architecture

Figure 2 illustrates the proposed system architecture for optimizing energy-efficient communication in smart cities, integrating LTE-M technology and an application server. LTE-M, a specialized cellular network for IoT devices, offers reliable long-distance communication. IoT devices transmit data over LTE-M to the application server, serving as the central hub for receiving, processing, and analyzing data. This application server orchestrates tasks such as data storage, analysis, and decision-making, enabling efficient information exchange and real-time actions and supporting smart city applications for improved energy efficiency and sustainability.

3.1 NB-IoT

Narrowband IoT (NB-IoT) is a specialized communication technology for IoT applications operating on existing cellular networks. It offers low-power, wide-area coverage, enabling efficient communication over long distances. In smart cities, NB-IoT conserves energy and ensures reliable communication, making it ideal for applications like smart metering and environmental monitoring. Its ability to penetrate obstacles ensures connectivity even in challenging settings. NB-IoT finds applications across industries, such as agriculture for precision farming and healthcare for remote patient monitoring. The research optimizes NB-IoT communication protocols to address energy consumption challenges in IoT deployments, aiming for sustainable and scalable solutions. This technology contributes to smart city initiatives, enhancing urban living conditions through energy savings and improved connectivity.

3.2 Duty Cycling

$$Duty\ Cycle\ (\%) = \frac{Active\ Time}{Active\ Time + Sleep\ Time} \times 100 \quad (1)$$

Duty cycling allows IoT devices to alternate between active and sleep modes, aiming to conserve energy. Equation 1 calculates the duty cycle, representing the proportion of time a device spends actively transmitting or receiving data versus the total time, including both active and sleep periods. Active Time is when the device is actively transmitting or receiving data, while Sleep Time is when it's in a low-power sleep mode. Adaptive duty cycling enables devices to adjust their active and sleep durations based on their requirements. This ensures devices wake up only when necessary to send or receive data, then promptly return to sleep, minimizing power consumption. Maximizing sleep time and minimizing active time reduces overall energy usage. For instance, a sensor might wake up every few minutes to send data instead of remaining on continuously. Adaptive duty cycling enables devices to be responsive when needed while using minimal energy, a crucial strategy for energy-efficient communication in smart cities with NB-IoT technology.

3.3 Data Aggregation

Data aggregation groups small data bits locally before transmission, providing two key benefits. Firstly, it decreases the frequency of data transmissions, leading to lower energy consumption by devices. Secondly, it reduces the overall data volume, optimizing network bandwidth use. For instance, in a network of temperature sensors across a city, instead of each sensor sending individual readings every few minutes, they can collect readings in a specific area and send them as a single message. This minimizes transmissions and lowers the overall data sent over the network. In the context of smart cities using Narrowband IoT technology, data aggregation is crucial for energy-efficient communication. It effectively minimizes energy consumption while supplying essential data for city management systems. This reduction in data transmission frequency and volume enables devices to conserve power, extend battery life, and contribute to the overall sustainability of smart city infrastructure.

3.4 Adaptive Transmission Power Control

Adaptive Transmission Power Control is akin to adjusting your voice volume based on your proximity and audience. Similarly, in IoT, devices dynamically tweak their signal strength depending on their distance from the receiver, like a base station. This smart adjustment helps devices conserve energy by not shouting when close to the base station and ensuring a clear, audible signal when farther away. In smart cities, where IoT devices span vast areas, this adaptive control is crucial. It optimizes communication efficiency, saving energy and enhancing the overall sustainability of the city's network. In essence, it's a savvy method to facilitate effective communication without unnecessary power wastage in smart city setups. In IoT communication, devices dynamically adapt their transmission power. When close or with a strong signal, power is reduced to save energy; when distant or with a weak signal, power is increased for reliable transmission. In smart cities with diverse signal strengths and distances, Adaptive Transmission Power Control optimizes energy usage. This dynamic adjustment ensures efficient data transmission, minimizing energy consumption while extending the

communication range. This optimization strategy, using NB-IoT technology, contributes significantly to reducing energy consumption and enhancing the sustainability of IoT deployments in smart cities. It strikes a balance between energy efficiency and communication reliability, allowing IoT devices to operate effectively while conserving resources.

3.5 Protocol Optimization

Protocol optimization improves communication efficiency, particularly in energy-sensitive networks like NB-IoT. Picture communication protocols as device instructions, detailing how devices initiate, conclude conversations, format messages, and manage errors. In NB-IoT networks within smart cities, protocol optimization streamlines these instructions to reduce energy waste and enhance overall performance. A common approach is minimizing protocol overhead, cutting unnecessary information, and simplifying steps, such as shorter messages or streamlined connection establishment. Fine-tuning protocols for NB-IoT characteristics, like narrow bandwidth and long-range communication, is a crucial optimization aspect. In this work, the Constrained Application Protocol (CoAP) is adapted to maximize efficiency and minimize energy consumption. Researchers optimizing communication protocols help smart city IoT devices communicate effectively, extending battery life and enhancing overall sustainability and reliability.

$$EC_{Reduction} = \frac{Initial_{EC} - Final_{EC}}{Initial_{EC}} \times 100 \quad (2)$$

Here, $EC_{Reduction}$ represents the percentage reduction in energy consumption achieved through the optimization process. $Initial_{EC}$ is the energy consumption of IoT devices using the original communication protocols. $Final_{EC}$ is the energy consumption of IoT devices after implementing optimized communication protocols. Equation 2 quantifies the percentage reduction in energy consumption achieved by optimizing communication protocols for IoT devices in smart cities using NB-IoT. This equation compares initial and final energy consumption, providing a measure of optimization effectiveness. Understanding the impact of research and demonstrating the benefits of energy-efficient communication protocols in smart city deployments is crucial.

IV. RESULTS

This research on energy-efficient communication protocols for IoT devices in smart cities using NB-IoT has unveiled key findings. Adaptive duty cycling, alternating between active transmission and sleep intervals, significantly reduces device active time, maximizing sleep intervals for energy savings without compromising reliability. Data aggregation techniques effectively decrease data transmissions, contributing to energy efficiency. Adaptive power control adjusts transmission power based on signal strength and distance, improving energy efficiency in smart city environments. Protocol optimization, including streamlining communication protocols and optimizing data transmission efficiency, has demonstrated substantial energy consumption reductions. Optimizing network topology by deploying infrastructure for optimal coverage has further contributed to energy savings. These strategies collectively enhance energy efficiency and sustainability in smart city IoT deployments using NB-IoT. These findings emphasize the effectiveness of optimization strategies in achieving energy efficiency in smart cities. Adoption of optimized communication protocols allows smart cities to significantly reduce energy consumption while supporting reliable communication and diverse IoT applications. These advancements contribute to sustainability goals and foster widespread adoption of energy efficient IoT solutions in urban environments as smart cities expand their IoT infrastructure. The implementation of optimized communication protocols is crucial for maximizing energy efficiency, improving resource utilization, and enhancing overall quality of life for residents in evolving smart cities.




Fig. 3. Comparison of energy consumption

Figure 3 provides a visual representation of the comparison between the initial and final energy consumption of IoT devices using communication protocols. The blue bar represents the initial energy consumption value, and the green bar represents the energy consumption after implementing optimized communication protocols. The chart clearly illustrates the reduction in energy consumption achieved through protocol optimization, highlighting the efficiency gains in the communication processes of IoT devices. Lower value on the y-axis indicates a more energy-efficient system, showcasing the positive impact of the optimization efforts on overall energy consumption.




Fig. 4. Comparison of Energy Consumption Reduction by Optimization Strategies

Figure 4 depicts the impact of optimization strategies on energy consumption for IoT devices in smart cities using NB-IoT. Each bar corresponds to a specific strategy, representing the percentage reduction in energy consumption achieved. The horizontal axis displays evaluated strategies, including Duty Cycling, Data Aggregation, Adaptive Power Control, Protocol Optimization, and Network Topology Optimization. The vertical axis indicates the percentage of energy consumption reduction, with longer bars indicating more effective strategies. Adaptive Power Control led with a 25% reduction, followed by Network Topology Optimization at 22%. Duty Cycling, Data Aggregation, and Protocol Optimization also contributed significantly, achieving reductions between 15% and 20%.

Table 1 Energy Consumption Reduction by NB-IoT Protocol Optimization Strategies

Optimization Strategy	Energy Consumption Reduction (%)
Duty Cycling	20
Data Aggregation	15
Adaptive Power Control	25
Protocol Optimization	18
Network Topology Optimization	22

Table 1 displays the results of various strategies for reducing energy consumption in smart city IoT deployments using Narrowband IoT (NB-IoT) technology. Each row corresponds to a specific optimization strategy, showing the percentage of energy consumption reduction achieved. Optimization strategies encompass techniques for refining energy-efficient communication protocols in smart city IoT devices. The Energy Consumption Reduction column indicates the percentage decrease compared to the baseline.

- Duty cycling alternates between active transmission and sleep intervals, resulting in a 20% reduction in energy consumption.
- Data Aggregation combines and summarizes data locally before transmission, achieving a 15% reduction in energy consumption.
- Adaptive Power Control adjusts transmission power based on signal strength and distance, leading to a 25% reduction in energy consumption.
- Protocol Optimization streamlines communication protocols, reducing unnecessary overhead and achieving an 18% reduction in energy consumption.
- Network Topology Optimization optimizes network infrastructure deployment for optimal coverage with a 22% reduction in energy consumption.

These findings underscore the effectiveness of diverse optimization strategies in enhancing energy efficiency in smart city IoT deployments using NB-IoT technology. Implementing these strategies enables cities to significantly cut energy consumption while ensuring reliable communication, contributing to sustainability and resource conservation efforts.




Fig 5. Adaptive transmission power control

Figure 5 shows the impact of adaptive transmission power control on signal strength in an IoT communication scenario. The x-axis represents the distance of IoT devices from the base station, while the y-axis indicates signal strength. The blue line represents signal strength without adaptive power control, while the orange line shows signal strength with adaptive power control. Red markers on the graph highlight specific points where adaptive adjustments were made, resulting in improved signal strength. From this graph, it is

evident that the proposed model enhances energy efficiency and ensures reliable communication across varying distances in the IoT network.

Table 2. Protocol optimization results

Metric	Before optimization	After optimization	Efficiency Gain (%)
Average message length (bytes)	150	120	20
Number of steps in communication	8	5	38.5
Overall efficiency gain	-	-	18.75

Table 2 quantifies the tangible improvements in communication efficiency achieved through the optimization of communication protocols in an IoT system. The metrics presented in the table highlight key aspects of protocol overhead reduction, emphasizing the impact on message length, the number of steps in the communication process, and an overall efficiency gain percentage. The table illustrates the average size of messages exchanged before and after protocol optimization. The reduction in average message length, from 150 to 120 bytes, signifies a more streamlined and efficient data transmission process. The number of steps involved in the communication process is crucial for assessing protocol efficiency. The table showcases a decrease from 8 to 5 steps after optimization, indicating a simplified and more direct communication pathway. The overall efficiency gain percentage is a composite measure, considering multiple metrics to provide a comprehensive view of the optimization impact. In this example, an efficiency gain of 18.75% reflects the cumulative improvement achieved across different aspects of communication protocol optimization. These metrics collectively demonstrate the success of protocol optimization in reducing protocol overhead, enhancing communication efficiency, and contributing to the overall optimization of the IoT system. The presented data underscores the positive outcomes of protocol refinement, showcasing its role in creating a more streamlined, resource-efficient, and effective communication framework for IoT devices.

V. CONCLUSION AND FUTURE SCOPE

In conclusion, this research concentrated on optimizing energy-efficient communication protocols for IoT devices in smart cities, specifically utilizing NB-IoT technology. The proposed structured framework and the integrated system architecture combining LTE-M technology and an application server for efficient communication underscore the importance of sustainability and reliability. The results unveiled significant accomplishments through various optimization strategies, with Adaptive Power Control leading with a 25% reduction, followed closely by Network Topology Optimization at 22%. Duty Cycling, Data Aggregation, and Protocol Optimization also contributed substantially, achieving reductions between 15% and 20%. Visual representations and a comprehensive table further illustrate the impact of these strategies on energy consumption reduction. This work lays the groundwork for future research in smart city IoT deployments. Subsequent exploration could focus on refining existing strategies, exploring additional optimization techniques, and extending the applicability of these findings to different IoT scenarios. The implementation of these energy-efficient communication protocols is essential for realizing sustainable and resource-conserving smart cities.

REFERENCES

- [1] Abbas, Ahmed M., Khaled Y. Youssef, Imbaby I. Mahmoud, and Abdelhalim Zekry. "NB-IoT optimization for smart meters networks of smart cities: Case study." *Alexandria Engineering Journal* 59, no. 6 (2020): 4267-4281.
- [2] Migabo, Emmanuel M., Karim D. Djouani, and Anish M. Kurien. "The narrowband Internet of Things (NB-IoT) resources management performance state of art, challenges, and opportunities." *IEEE Access* 8 (2020): 97658-97675.
- [3] Popli, Sakshi, Rakesh Kumar Jha, and Sanjeev Jain. "A survey on energy efficient narrowband internet of things (NB-IoT): architecture, application and challenges." *IEEE Access* 7 (2018): 16739-16776.
- [4] Migabo, Munguakonkwa Emmanuel. "Energy efficient and scalable channel coding and clustering approach for Narrowband Internet of Things (NB-IoT)." PhD diss., Université Paris-Est; Tshwane University of Technology, 2021.
- [5] Bali, Malvinder Singh, Kamali Gupta, Kanwalpreet Kour Bali, and Pramod K. Singh. "Towards energy efficient NB-IoT: A survey on evaluating its suitability for smart applications." *Materials Today: Proceedings* 49 (2022): 3227-3234.
- [6] Tsoukaneri, Galini, Francisco Garcia, and Mahesh K. Marina. "Narrowband IoT Device Energy Consumption Characterization and Optimizations." In *EWSN*, pp. 1-12. 2020.
- [7] Rastogi, Eshita, Navrati Saxena, Abhishek Roy, and Dong Ryeol Shin. "Narrowband internet of things: A comprehensive study." *Computer networks* 173 (2020): 107209.
- [8] Yassine, Farah, Melhem El Helou, Samer Lahoud, and Oussama Bazzi. "Energy-Efficient Uplink Scheduling in Narrowband IoT." *Sensors* 22, no. 20 (2022): 7744.

- [9] Manzar, Syed Ariz, Shilpi Verma, and Sindhu Hak Gupta. "Analysis and optimization of downlink energy in NB-IoT." *Sustainable Computing: Informatics and Systems* 35 (2022): 100757.
- [10] Chen, Min, Yiming Miao, Yixue Hao, and Kai Hwang. "Narrow band internet of things." *IEEE access* 5 (2017): 20557-20577.
- [11] Pirayesh, Hossein, Pedram Kheirkhah Sangdeh, and Huacheng Zeng. "EE-IoT: An energy-efficient IoT communication scheme for WLANs." In *IEEE INFOCOM 2019-IEEE Conference on Computer Communications*, pp. 361-369. IEEE, 2019.
- [12] Rajab, Husam, and Tibor Cinkler. "Enhanced Energy Efficiency and Scalability in Cellular Networks for Massive IoT." *5G and Beyond* (2023): 283.
- [13] Nauman, Ali, Muhammad Ali Jamshed, Yazdan Ahmad Qadri, Rashid Ali, and Sung Won Kim. "Reliability optimization in narrowband device-to-device communication for 5G and beyond-5G networks." *IEEE Access* 9 (2021): 157584-157596.
- [14] Perumal, G., Subburayalu, G., Abbas, Q., Naqi, S. M., & Qureshi, I. (2023). VBQ-Net: A Novel Vectorization-Based Boost Quantized Network Model for Maximizing the Security Level of IoT System to Prevent Intrusions. *Systems*, 11(8), 436.
- [15] Satyanarayana, P., Diwakar, G., Subbayamma, B. V., Kumar, N. P. S., Arun, M., & Gopalakrishnan, S. (2023). Comparative analysis of new meta-heuristic-variants for privacy preservation in wireless mobile adhoc networks for IoT applications. *Computer Communications*, 198, 262-281.
- [16] Kumar, Voruganti Naresh, Vootla Srisuma, Suraya Mubeen, Arfa Mahwish, Najeema Afrin, D. B. V. Jagannadham, and Jonnadula Narasimharao. "Anomaly-Based Hierarchical Intrusion Detection for Black Hole Attack Detection and Prevention in WSN." In *Proceedings of Fourth International Conference on Computer and Communication Technologies: IC3T 2022*, pp. 319-327. Singapore: Springer Nature Singapore, 2023.
- [17] Hemanand, D., G. Vinoda Reddy, S. Sathees Babu, Kavitha Rani Balmuri, T. Chitra, and S. Gopalakrishnan. "An intelligent intrusion detection and classification system using CSGO-LSVM model for wireless sensor networks (WSNs)." *International Journal of Intelligent Systems and Applications in Engineering* 10, no. 3 (2022): 285-293.
- [18] Balmuri, Kavitha Rani, Srinivas Konda, Kola Thirupathaiiah, Voruganti Naresh Kumar, and Jonnadula Narasimharao. "A Nanoplasmonic Ultra-wideband Antenna for Wireless Communications." In *Evolution in Signal Processing and Telecommunication Networks: Proceedings of Sixth International Conference on Microelectronics, Electromagnetics and Telecommunications (ICMEET 2021), Volume 2*, pp. 503-510. Singapore: Springer Singapore, 2022.