

¹ Ms.Meeta
Bakuli

² Dr. Rahul
Pethe

Energy Efficiency Enhancement of Next Generation Mobile Systems- An Hybrid Approach



Abstract: - The surge in mobile users and online applications, particularly video streaming, is indeed fueling a significant increase in global data traffic. To accommodate this growth while ensuring fast data rates, it's crucial to optimize data transmission with limited resources. Balancing high data throughput with lower power consumption is essential for network efficiency without compromising Quality of Service (QoS).

In our research, we focus on enhancing data transmission efficiency between base stations and multiple users. Our approach revolves around transmitting data only when there's a demand or explicit user request, a strategy aimed at conserving power. By doing so, we achieve substantial energy savings, leading to decreased energy consumption and improved energy efficiency.

Central to our methodology is an optimized power control transmission mechanism. This ensures that data rates and QoS requirements are met while maximizing energy efficiency (EE). By dynamically adjusting power levels based on transmission needs, we strike an optimal balance between throughput and power consumption.

Our findings underscore the significance of adaptive power control strategies in modern wireless networks. By intelligently managing resources and minimizing unnecessary transmissions, we pave the way for sustainable network growth and enhanced user experiences.

Keywords: Energy Efficiency, Quality of Service, Data throughput.

1. Introduction

The escalating demand for data, driven by the rapid increase in mobile users worldwide, presents a formidable challenge for network providers. With data consumption growing by nearly 40% compared to the last five years, the strain on network resources is substantial. To address this challenge, it's imperative to design energy-efficient networks that can meet the demand for high data throughput while adhering to Quality of Service (QoS) requirements.

The concept of On-Demand data transfer plays a crucial role in achieving this balance. By establishing connections and transferring data only when necessary, energy consumption is minimized, leading to enhanced energy efficiency. This approach not only mitigates environmental concerns associated with energy consumption but also helps manage the escalating costs of network operations.

Furthermore, employing On-Demand Power Control techniques ensures that data rates and QoS expectations are optimized. By dynamically adjusting power levels based on transmission needs, network efficiency is maximized, resulting in an optimal utilization of limited resources.

In summary, the development of energy-efficient networks capable of providing high data throughput while maintaining QoS standards is essential to meet the growing demand for data. Leveraging On-Demand data transfer and Power Control techniques represents a significant step towards achieving this goal, ensuring sustainable network growth in the face of escalating data demands.

2. Literature Review

The pursuit of enhanced Transmitted Energy Efficiency and data throughput within the constraints of limited network resources has been a focal point of global research efforts. Researchers have explored various methods to achieve these objectives, including Transmit Power Control. Regulating the transmitted power helps optimize energy efficiency. This approach ensures that the required signal strength is maintained while minimizing unnecessary power consumption.

Small Cell Technology: Implementing small cell networks enables more efficient use of available spectrum and resources. By reducing the coverage area of each cell, small cell technology can alleviate congestion and enhance energy efficiency.

Massive MIMO (Multiple-Input Multiple-Output): Leveraging multiple antennas at both the transmitter and receiver ends, massive MIMO technology maximizes spectral efficiency and enhances energy efficiency by improving signal quality and reducing interference.

Power Consumption Reduction: Efforts to reduce overall power consumption are essential for improving energy efficiency. This can involve optimizing hardware components, implementing energy-saving algorithms, and adopting energy-efficient protocols.

¹ Asst. Prof. (Dept of E&TC), G.H.R.C.E.M, Pune,India. Email: meeta.bakuli@raisoni.net

² Asst.Prof.(Dept of E&TC), G.H.R.I.E.T, Nagpur,India. Email: rahul.pethe@raisoni.net

Copyright © JES 2024 on-line : journal.esrgroups.org

The overarching goal of improving energy efficiency is not only to mitigate environmental impact but also to minimize energy costs associated with network operation. Achieving energy efficiency without compromising Quality of Service (QoS) standards is paramount. Research has delved into various aspects of this challenge, including: Orthogonal Frequency Division Multiple Access (OFDMA): OFDMA-based LTE systems offer a flexible framework for accommodating diverse user QoS requirements. By efficiently allocating resources based on user demand, OFDMA systems can maintain QoS, while maximizing energy efficiency. Resource Allocation Schemes: Developing optimal resource allocation schemes is critical for maximizing energy efficiency. These schemes dynamically allocate network resources such as bandwidth, power, and time slots to users based on their requirements, ensuring efficient utilization of limited resources.

3. System Description

The utilization of on-demand power allocation relies on effective coordination between the base station and the mobile users accessing the network. Additionally, coordination between cells and base stations is crucial for optimizing network performance. Let's consider a scenario where we have a set of mobile users and a Macro Base station, as illustrated in Fig 1.

To efficiently manage the available bandwidth, we divide the total channel bandwidth into smaller sub-bands, each containing a set of subcarriers. This division helps mitigate interference between different frequency bands. Each sub-band is allocated a separate subcarrier to ensure interference-free transmission.

In this context, it's essential to assume that the base station possesses perfect Channel State Information (CSI). This means that the base station has accurate knowledge of the channel conditions, enabling it to make informed decisions regarding power allocation and resource management.

With this setup, effective coordination between base stations and mobile users, as well as inter-cell and inter-base station coordination, becomes paramount. By leveraging the perfect CSI, the base station can dynamically allocate power and resources based on real-time channel conditions and user demand, thereby optimizing energy efficiency and ensuring Quality of Service (QoS) requirements are met.

Overall, the integration of on-demand power allocation with coordinated resource management strategies facilitates efficient utilization of network resources, ultimately enhancing network performance and user experience.

3.1. Signal model




Fig 1: A Communication Network with one Macro cell Base Station with no of mobile users.[1]

If we have i mobile users and i sub-channels, the output for the i th channel and the i th user can be represented as follows:

Let's denote:

x_i = input signal for the i th user

h_i = channel frequency response for the i th channel and

y_i = as the output signal for the i th channel and the i th user.

Then, the output y_i for the i th channel and i th user can be expressed using the concept of linear convolution in the frequency domain:

$$y_i = h_i * x_i$$

Where:

- $*$ denotes convolution,

In practical scenarios, this convolution operation accounts for the effect of channel fading, noise, and interference on the transmitted signal, resulting in the received signal at the receiver end. The output signal y_i represents the received signal for the i th user after passing through the channel.

Also y_i is given by

$$y_i = \sqrt{p_i} \cdot h_i \cdot x_i + I_i + N_0 \quad (1)$$

$$\forall i \in \{1, 2, 3, \dots, n\}$$

Where

$$I_i = \sqrt{a_i} \cdot p_i \cdot h_i \cdot x_i \dots \dots \dots (2)$$

$$\forall i \in \{1, 2, 3, \dots, n\}$$

where

p = Transmitted Power

x = Input

N_0 = Noise

I = Adjacent channel frequency Interference.

Then, the data rate or the throughput is given by

$$R_i = B \log_2 \left(1 + \frac{S}{N} \right) \quad (3)$$

$$\forall i \in \{1, 2, 3, \dots, n\}$$

Where B = Bandwidth

S/N = Signal to Noise ratio

3.2. Power model

The total power consumption of a base station is given by

$$PC = P_{amp} + P_{circuit} \quad (4)$$

PC = Total Power Consumed

P_{amp} = Power consumed by the Power amplifiers

$P_{circuit}$ = Power consumed by the other circuit blocks such as the digital to analog converter, filters, mixer etc.

The $P_{circuit}$ is assumed to be constant, hence the total power Consumption is a variable term depending totally on the Power consumed by the Power amplifiers in the trans-receiver circuits

3.3. Energy Efficiency model

The Energy Efficiency (EE) of a base station is given by the ratio of Data rate or throughput and the total power consumed i.e

$$EE = \frac{R_i}{PC} \quad (5)$$

$$\forall i \in \{1, 2, 3, \dots, n\}$$

Where R = data rate or throughput

& PC = Total power consumed

3.4. Quality of Service model :-

The Quality of Service (QOS) is given by

$$Q_i = 1 - 1/2 \exp [(-R_i - R_{th}) / R_{th}] \quad (6)$$

$$\forall i \in \{1, 2, 3, \dots, n\}$$

where R_i = data rate or data throughput for i users
& R_{th} = Threshold value of the data rate set.

Hence the Quality of Service is dependent on the data rate obtained which is compared to the threshold value or the set value of the data rate.

3.5. On-Demand Energy Efficiency Model

The On-Demand Energy Efficiency is given by

$$EE(D) = EE_i \cdot Q_i \quad (7)$$

where $i \in \{1, 2, 3, \dots, n\}$

Where $EE(D)$ is the On-Demand Energy Efficiency

EE_i = The total Energy Efficiency of i users

Q_i = Quality of Service of i users.

The max $EE(D)$ is defined as

$$EE(D)_{max} = \sum_{i=1}^n \text{Blog}_2(1 + P_{transmitted}) / (P_{Ci})$$

Where B = channel bandwidth

Hence in order to achieve max $EE(D)$, the power transmitted should be maximum and the Power Consumption should be minimum.

Therefore for $EE(D)_{max}$, we control the max power transmitted in order to achieve a max Energy Efficiency while decreasing the power consumption.

4. The On Demand Power Control

Algorithm

Steps:

1. Initialize the time $t = \text{max}$ and set $t = 0$
 2. Initialize the transmitted power $P_t = 0$
 3. Initialize the requirement of the users $i = 0$
 4. Sense the requirement of the user by setting the particular user = 1
 5. Update the value of P_t for the particular user
 6. Compute $EE(D)_{max}$, Q_i
- according to (7), (8) and (6) resp
7. Compare the P_t with the $P_t \text{ max}$ (max threshold value)
 8. If $P_t < P_t \text{ max}$, then
 9. $P_t = P_t \text{ max}$
 10. Repeat for all users
 11. update $t = \text{max}$

5. Simulation results

The simulation is done considering a Base station with $n = 10$ subcarriers, a total bandwidth $B = 10$ MHz, $P_{Ci} = 0.2$ W and a max transmit power $P_t \text{ max} = 10$ W for 3, 5 & 10 Users resp.




Fig 2: $P_t \text{ max}$ Vs $EE(D)_{max}$

Fig 2 shows $P_t \text{ max}$ Vs $EE(D)_{max}$ with $d = 20$ km and $d = 40$ km for one Macro Cell Base Station

- i) In fig 2,, it shows that the On-Demand Energy Efficiency -EE (D)max is 350 M bits / W for 3 Mobile Users at a distance d= 20km
 - ii) The On-Demand Energy Efficiency- EE (D)max reduces to 175 M bits / W for 3 Users for a distance d= 40km
 - iii) If the no of mobile users increases then EE (D)max decreases to 200 M bits / W for 5 Mobile Users at a distance d = 20km
 - iv) Further the EE (D)max decreases to 100 M bits / W for 5 Mobile Users at a distance d = 40km
- Thus the Energy Efficiency-EE (D)max achieved is high i.e. 350Mbits/W for a transmitted Power of 1W to 10W by controlling On-Demand Transmit Power ,increasing the Energy Efficiency.




Fig 3: Pt max Vs QOS degree with d=20km and d= 40km for One Macro cell Base Station.

Fig 3 shows the transmitted power Vs the Quality of Service.(QOS) satisfaction degree, which lies between min 0 and max 1 value.

- i) In the fig 3, it shows that QOS satisfaction degree is max i.e. 0.7 for 3 Mobile users at a distance d = 20km
 - ii) The QOS satisfaction degree decreases to 0.35 for 3 Mobile users, when the distance increases to d = 40km
 - iii) Whereas the QOS satisfaction degree for 5 Mobile users is 0.2 for 5 Mobile users for a distance d = 20km
 - iv) The QOS satisfaction degree is min at 0.42 for 5 Mobile users for a distance d = 40km
- Thus the QOS satisfaction degree achieved is highest i.e. . 0.7 for 3 Mobile users at a distance d = 20km for a transmitted Power of 1W to 10W




Fig 4: Pt max Vs Date rate variance with d= 20km and d = 40km for one Macro Cell Base Station.

- i) In fig, 4, it shows that the data rate variance is min i.e. $0.45 * 10^{-20}$ for 3 Mobile users for a distance d = 20km
- ii) Which increases to $0.5 * 10^{-20}$ for 5 Mobile users for a distance d = 20km at Pt = 3 W
- iii) The data rate variance is $1.75 * 10^{-20}$ for 3 Mobile Users for d = 40km
- iv) It increases to max. $2.0 * 10^{-20}$ for 5 Mobile Users for d = 40km

6. Conclusion

Using On-Demand Transmit Power Control for transmitting data bits from the base station to end users maximizes energy efficiency while maintaining optimal Quality of Service and data rates, primarily by regulating power consumption in power amplifiers.

Simulated results demonstrate that Energy Efficiency peaks at 350 M bits / W for 3 Mobile Users at a distance $d = 20\text{km}$ for one macro cell base station with On-Demand transmit power control, surpassing continuous power transmission from base stations to users. Additionally, Quality of Service satisfaction is max i.e. 0.7 for 3 Mobile users at a distance $d = 20\text{km}$ across a significant power transmission range from 4W to 10W.

Furthermore, data rate variance is minimal at maximum transmitted power, ensuring a stable data bit rate for end users.

REFERENCES

- [1] Yulan Gao, Yue Xiao (2019) Energy Efficient Power Allocation with OFDMA Downlink Transmission *IEEE Trans. Wireless Commun.*, vol. 18, no. 4, pp. 2141–2155,
- [2] Y. Y. Shen, C. X. Jiang, T. Q. S. Quek, and Y. Ren (2018). Device-to-device-assisted communications in cellular networks: An energy efficient approach in downlink video sharing scenario *IEEE Trans. Wireless Commun.*, vol. 17, no. 3, pp. 2054–2067
- [3] Jihwan Kim, Hyang-Won Lee, Song Chong (2018). Traffic-Aware Energy-Saving Base Station Sleeping and Clustering in Cooperative Networks *IEEE Trans. Wireless Commun.*, vol. 17, no.2, pp. 1173–1186
- [4] Gozde Ozcan, Mustafa Ozmen, M. Cenk Gursoy (2017). QoS-Driven Energy-Efficient Power Control With Random Arrivals and Arbitrary Input Distributions *IEEE Trans. Commun.*, vol. 16, no. 1, pp. 376–388
- [5] Wenjun Xu Xuemei Zhou Chia-Han Lee, Zhiyong Feng and Jiaru Lin(2016). Energy-Efficient Joint Sensing Duration, Detection Threshold, and Power Allocation Optimization in Cognitive OFDM Systems *IEEE,Trans. Commun.*, vol. 15, no. 12, pp. 8339–8352
- [6] Jian L.,Jingxian Wu, Mugen PengandPing Zhang (2016). Queue-AwareEnergy-Efficient Joint RemoteRadio Head Activation and Beamforming in Cloud RadioAccessNetworks *IEEE Trans. Wireless Commun.*, vol. 15, no. 6, pp.3880–3894
- [7] Siqian Cui, Homayoun Yousefi'zadeh,and Xuemai Gu, (2016). An Optimal Power Control Algorithm for STDMA MAC Protocols in Multihop Wireless Networks *IEEE Trans. WirelessCommun.*, vol. 15, no. 5, pp. 3131–3142,
- [8] Yichao Chen, Shibo He, Fen Hou, Zhiguo Shi and Jiming Chen (2018). An Efficient Incentive Mechanism for Device-to-Device Multicast Communication in Cellular Networks *IEEE Wireless Commun.*, vol. 17, no. 12, pp. 7922–7935
- [9] Markus Klügel, Wolfgang Kellere (2018). The Device-to-Device Reuse Maximization Problem With Power Control *IEEE Commun. Surveys Tut.*, vol. 17, no. 1, pp. 1836–1848,
- [10] Venturino, A. Zappone, and C. Risi, S. Buzzi (2015). Energy-efficient scheduling and power allocation in downlink ofdma networks with base station coordination *IEEE Trans. Wireless Commun.*, vol. 14, no.1,pp.1–14
- [11] Chen and J. Zhao (2014). The requirements, challenges and technologies for 5 G of terrestrial mobile telecommunication *IEEE Comm Mag.*, vol. 52, no.5,pp. 36–43
- [12] Vaezy, M.J. Omid, M.M.Naghsh ,and H Yanikomeroglu (2019). Energy-efficient, transceiver design MIMO interference channels mobile telecommunication *IEEE Trans. Commun.*, vol. 67, no.8,pp. 5377-5389
- [13] A-A. Lu, X. Gao, W.Zhong and C. Xiao, and X.Meng (2019). Robust transmission for massive MIMO downlink with imperfect CSI *IEEE Trans. Commun.*, vol. 67, no.8,pp. 5362–5376
- [14] Q.D.Vu, L.N.Tran, M.Juntti, and E.K.Hong, (2015). Energy Efficient bandwidth and power allocation for multi-homing networks *IEEE Trans. Signal Process.*, vol. 63, no.7,pp. 1684-1699
- [15] K.G. Nguyen, Q.D.Vu, M.Juntti, and L. N.Tran (2017). Distributed solutions for energy efficiency fairness in multicell MISO downlink *IEEE Trans. Wireless Commun.*, vol. 16, no.9,pp. 6232–6247
- [16] Zhang,Li,C.X.wang,Y.Ruan,Y.Fu and H. Zhang (2018). Energy-spectral efficiency trade-off in underlaying mobile D2D communications: An economic efficiency perspective *IEEE Trans. Wireless Commun.*, vol. 17, no.7,pp.4288–4301
- [17] F. Rosas et al, (2016). Optimizing the code rate of energy-constrained wireless communications with HARQ *IEEE Trans. Wireless Commun.*, vol. 15, no.1,pp. 191–205
- [18] E. Eraslan and B. Daneshrad, (2017). Low-complexity link adaptation for energy efficiency maximization in MIMO-OFDM systems *IEEE Trans. Wireless Commun.*, vol. 16, no.8,pp. 5102–5114
- [19] Z. Yang, Z. Ding, P.Fan and N.Al-Dhahir, (2016). A general power allocation scheme to guarantee quality of service in downlink and uplink NOMA systems *IEEE Trans. Wireless Commun.*, vol. 15, no.11,pp. 7244–7257
- [20] Anis Ouni, Hervé Rivano, Fabrice Valois, and Catherine Rosenberg, (2015). Energy and Throughput Optimization of Wireless Mesh Networks With Continuous Power Control *IEEE Trans. Wireless Commun.*, vol. 14, no.11,pp. 1131–1142.