

¹Dr Prasad Rayi,
²Paidimalla Naga
 Raju,
³Raghu Kalyana,
⁴D.N.V.S.Vijaya
 Lakshmi

Deep Learning for Signal Processing in Communication Systems



Abstract:

The significant demands placed on contemporary communication systems have prompted a reassessment of the established and comprehensive communication theory. The obsolescence of present system implementations is contentious, yet they may adapt to problems when integrated with new technology. The concept of formulating wholly new methodologies has also emerged. Recent advancements in machine learning, particularly in deep learning methodologies, provide potential new avenues for study. This study elucidates the rationale for the incorporation of deep learning in communications.

The report delineates the present research methodologies. Emphasis is placed on examining many domains of appliances and delineating their merits and demerits, including the development of comprehensive communication systems such as autoencoders and the role of neural networks in signal recognition and modulation categorization. The findings suggest significant promise for deep learning applications in communications inside suboptimal domains.

Keywords—Communication System; Deep Learning; End-to-End System; Autoencoder; Neural Network; Modulation Classification

Introduction

Contemporary communication methods have prompted creative needs. The escalating demand for quality service, the rising number of connected devices, the vast volume of data requiring high-speed transfer, the necessity for minimal response latency (real-time communication), and the imperative to uphold requisite security measures constitute significant challenges that must be addressed. The densification and expansion of wireless networks present a series of energy efficiency concerns [1]. The current inadequate user capacity and the lack of spectrum resources must be addressed, maybe via dynamic spectrum access and cognitive radio.

Despite possessing robust underpinnings in information theory and statistics, current communication technology solutions fail to meet contemporary demands. Conventional communication systems struggle to adjust to extremely varied channel circumstances due to algorithms that are often tailored for mathematically convenient models.

Deep learning methodologies have shown encouraging outcomes across several domains, including computer vision tasks such as picture segmentation, classification, colorization, and object identification, as well as natural language processing applications like voice recognition and sentiment analysis.

Researchers have begun the integration of machine learning, particularly the deep learning subset, with communication technologies.

^{1,2,3,4}International School Of Technology And Sciences For Women, A.P, India.

The fundamental purpose of communication is to convey information from the source to the recipient while preserving its significance.

Consequently, the primary issue of communication is the precise or approximate replication of a message originating from a distinct location. Although proponents of conventional communication system solutions express skepticism about the requirement of the technique, it is posited that machine learning may augment communications primarily in terms of capacity and data rates by effectively managing substantial volumes of communication data. Investigating machine assistance may provide dynamic and flexible communication systems that learn from spectrum data [8].

The subsequent sections of the paper are structured as follows. Section II delineates the general features of deep learning.

Section III elucidates the rationale for using deep learning in communications and presents a classification of research methodologies. Section IV discusses the findings of pertinent experimental endeavors. The document concludes with a conclusion.

Deep Learning Fundamentals

Deep learning is a category of machine learning, which is a subset of artificial intelligence. Deep learning principles are derived from the operations of the human brain [10].

The fundamental components of all deep learning methodologies are artificial neurons linked inside a multi-layered artificial neural network. Neural networks are regarded as universal function approximators [11]. A collection of parameters (weights) that minimizes the approximation error (loss function) is established throughout the training phase. Every layer aids in feature extraction, hence facilitating pattern detection and uncovering regularities in data connections. Conversely, machine learning approaches cannot autonomously recognize patterns; they need human intervention in the process [12]. They also rely on statistical information derived from well-organized data exhibiting exact patterns.

The autonomous nature of fundamental deep learning techniques is widely valued, however numerous limitations are acknowledged. A substantial, appropriate dataset and considerable time are necessary for the training procedure, along with meticulous parameter optimization to achieve effective generalization. Attention is drawn to their skills in the effective modeling of complex probability distributions. Autoencoders are unsupervised neural networks, deep generative models that aim to replicate their input in the output. The encoder learns compressed representations of the input data, while the decoder structure tries to recreate the original data. Generative adversarial networks (GANs) include two neural networks: a generator that creates data mimicking actual data, and a discriminator that attempts to distinguish between authentic and produced data [13]. Generative Adversarial Networks (GANs) may facilitate the augmentation of limited training data.

Applications Of Deep Learning In Communication Systems

Communication theory seems to be highly advanced, with information seamlessly represented as a series of bits and communication system models established with clarity. Furthermore, any mistakes in communication systems are often mitigated by retransmissions. The assertion of these facts renders the use of deep learning in communications debatable.

However, practical real-life situations do not align with theoretical expectations. Despite the simplicity of

constructing communication channel models, determining the ideal complexity remains challenging [14]. Excessively simplified mathematical models fail to accurately represent the actual circumstances of the channel. The consequences that arise during signal propagation are often unknown. Excessively intricate models squander computational and temporal resources and often fail to generalize well due to their excessive adaptation to specific scenarios. Automated learning of input data properties, such as photographs, has shown superiority over human-engineered model development and decision-making in both quality and efficiency [14]. The execution of neural networks may be parallelized using multi-core and graphics processing unit (GPU) designs, resulting in rapid algorithm execution. These findings motivate more investigation into deep learning within the communication area.

Communication systems include several subsystems and components. Certain models are either improperly constructed or too intricate for real-time applications [14]. The local optimization of each block does not ensure the global optimality of the system [15]. Consequently, interest in a collaborative (end-to-end) implementation of communication systems has increased [16–19]. The unsatisfactory performance of individual blocks may be enhanced with the use of deep learning [15]. The categorization of experiments pertaining to deep learning and communications can be delineated into two distinct groups: - end-to-end communication system optimization, and - optimization of communication components (e.g., channel modeling, channel equalization, decoding, compression, demodulation, modulation recognition, etc.) [20].

Nevertheless, the categorization of the approaches may take into account their intrinsic reasons. Deep learning techniques in communications can be categorized based on their application into: methods that analyze the effects of architectural alterations in communication systems (end-to-end systems), methods that improve spectrum sensing (e.g., channel estimation, signal detection, modulation classification), and methods for wireless security [8].

Deep learning It is a sort of supervised machine learning whereby a model acquires the ability to execute classification tasks directly from pictures, text, or audio. Deep learning is often executed using a neural network. The word "deep" denotes the quantity of layers inside the network; a greater number of layers signifies a deeper network.

Results And Discussion

This section discusses the pros and drawbacks of the most significant outcomes across many application domains, taking into account the system building style.

A. End-to-end systems

The framework of a communication system typically comprises the transmitter, the channel, and the receiver. The transmitter and receiver consist of distinct blocks executing various operations [5]. In conventional communication technology, the optimization of blocks is conducted in isolation. Nonetheless, it is shown that the disjunction of source and channel coding fails to provide optimum outcomes [21]. Consequently, the representations of communication systems using autoencoders have been established [16–19]. The communication system shown as an autoencoder is seen in Fig. 1. This method renders block structures superfluous. A single message from a collection of potential messages is provided as input. The transmitter and receiver are constructed as feedforward neural networks of dense layers. The normalized output from the

transmitter is sent to a noise layer that simulates the channel. The softmax function in the receiver calculates the likelihood of each transmission. The final result is a forecast of the transmitted message; the message with the greatest likelihood.

Communication autoencoders have been trained on simulated data [16], [17] and validated via over-the-air broadcasts using software-defined radios (SDRs) [18]. Nonetheless, autoencoder implementations operate only using established gradient-based techniques that need differentiable mathematical expressions [19]. If channel characteristics are entirely unknown, the gradients cannot accurately backpropagate across the network. It is mentioned in [15] that reinforcement learning-based [19] and conditional GAN-based methodologies have been developed to address the problem. The proposal in [8] involves training the autoencoder using a stochastic channel model, followed by fine-tuning by transfer learning.




Figure 1. Communication system autoencoder representation [16]

An autoencoder requires little previous information, since the network acquires learning by the specified performance measure, such as block error rate (BLER) [8]. Figure 2 illustrates the Block Error Rate (BLER) in relation to the energy per bit to noise power spectral density ratio (E_b/N_0) achieved by the autoencoder (7,4) trained at $E_b/N_0 = 3$, alongside many baseline communication methodologies [16], [22]. The proximity of the BLER attained by the autoencoder (7,4) to the BLER obtained by Hamming (7,4) code with maximum probability decoding underscores the need for future investigation into the use of autoencoder architecture in communications. The primary benefit of autoencoder modeling in communications is its ability to learn combined coding and modulation schemes in an unsupervised way. Nonetheless, the intricacy of exceptional architectural design and meticulous parameter optimization make this technique challenging.

B. Signal detection and modulation classification

Employing deep learning to highlight essential characteristics of the process. The signal vector employed in the experiments comprises two bits encoded via quadrature phase-shift keying (QPSK), while the received signal is a combination of the transmitted signal and Gaussian noise with a variance of 2. A total of 40,000 received constellation points, along with the transmitted signal, are utilized for the training process. The detection areas of QPSK constellation points are generated using a trained neural network. It is concluded that neural networks cannot enhance signal detection, since the ideal technique for this task in an additive white Gaussian noise channel is already established: mapping the received point to the nearest area center based on Euclidean distance. The findings..

Although the authors contend that deep learning may not enhance traditional outcomes in channel estimation, multi-user multiple-input multiple-output (MIMO) processing, and transmit power allocation [14], they underscore that employing supervised learning on existing algorithmic solutions and inputs could diminish the complexity and resources required for algorithm implementation. As a result, latency limitations may achieve the target threshold of 1 ms or maybe decrease further. Nonetheless, time will be allocated to the design and training phases.




Figure 2. BLER versus E_b/N_0 for the autoencoder and traditional communication schemes [16], [22]

2) Modulation classification: Identifying the modulation format is a significant problem for several civilian and military applications [23]. A dataset of about 900,000 time frames $r(t)$ with 11 modulation classes has been generated to facilitate experimentation and enhance interest in modulation categorization using deep learning. Equation (1) delineates the simplified $r(t)$ as the summation of a modulated temporal signal $s(t)$, which is contingent upon the path loss constant C and noise $n(t)$:

The data closely replicate real-world signals due to the intricate modeling of $r(t)$, which incorporates various channel effects into the produced signals. The collection comprises eight digital modulations and three analog

modulations: BPSK, QPSK, 8-PSK, 16-QAM, 64-QAM, BFSK, CPFSK, PAM-4, WB-FM, AMSSB, and AM-DSB. A convolutional neural network (CNN) serves as their classifier [3], [22]. CNN is a specialized neural network designed for processing input using a grid-like architecture. The efficacy of categorization may be shown via a confusion matrix. Figure 4 presents a confusion matrix for 550 test frames from the dataset. Specifically, to reduce complexity, the CNN is trained using 5,500 time frames, each including 128 symbols over 12 epochs.




Figure 3. The detection regions of the QPSK signal obtained by neural network [12],

The signal-to-noise ratio (SNR) is established at 30 dB. The matrix demonstrates good outcomes. The network conflates 16-QAM with 64-QAM frames, since 16-QAM is a subset of 64-QAM. The network also conflates QPSK and 8-PSK frames owing to the resemblance of their constellation diagrams when subjected to phase rotation from the fading channel and frequency offset [22].

The primary benefit of training a CNN for modulation categorization is the elimination of user-guided procedures while attaining adequate accuracy. A CNN classifier demonstrates enhanced performance at reduced SNR. This information should facilitate a doubling.

Conclusion

The exploration of deep learning in communications remains mostly theoretical. As a result, several aspects remain unclear, such as appropriate data format, learning goals, loss functions, and training methodologies. The handy datasets are currently under development. Emerging demands for elevated data rates and a growing array of linked gadgets in communication systems guarantee the availability of substantial data, which may be used to create suitable datasets for neural network training. The conviction that deep learning cannot enhance the outcomes of existing communication theory principles affects the pace of ongoing research and overall interest in the domain.

Nevertheless, the executed tests demonstrate significant promise for its use, namely in end-to-end communication system modeling and modulation categorization. The findings indicate that a thorough analysis of the area of deep learning application is necessary due to the pre-existing optimized principles in communication technology. The essential domain knowledge must not be overlooked. The primary benefit of using deep learning in communications is the decrease in user effort.

Autoencoders provide the benefit of learning without pre-existing information. Nevertheless, particular emphasis must be placed on the architectural design. Neural network-based modulation categorization signifies a

prospective research avenue due to its commendable accuracy and degree of automation. However, the adaptation of existing methods to the simulated data indicates the use of semi-supervised approaches to get a more efficient classifier.

REFERENCES

1. R. L. G. Cavalcante, S. Stanczak, M. Schubert, E. A., and U. Tuerke, "Toward energy-efficient 5G wireless communications technologies: Tools for decoupling the scaling of networks from the growth of operating power," *IEEE Signal Processing Magazine*, vol. 31, no. 6, pp. 24–34, 2014.
2. M. Li and H. Li, "Application of deep neural network and deep reinforcement learning in wireless communication," *PLoS ONE*, vol. 15, no. 7, 2020.
3. T. O'Shea, J. Corgan, and T. C. Clancy, "Convolutional radio modulation recognition networks." <https://arxiv.org/abs/1602.04105>, 2016.
4. C. E. Shannon, "A mathematical theory of communication," *Bell System Technical Journal*, vol. 27, pp. 379–423, 623–656, 1948.
5. U. Madhow, "Introduction to communication systems," Cambridge: Cambridge University Press, 2014.
6. N. O' Mahony, S. Campbell, A. Carvalho, S. Harapanahalli, G. Velasco- Hernandez, L. Krpalkova, D. Riordan, and J. Walsh, "Deep learning vs. traditional computer vision," in *Advances in Computer Vision Proceedings of the 2019 Computer Vision Conference (CVC)*, pp. 128–144, 2019.
7. P. Wlodarczak, J. Soar, and M. Ally, "Multimedia data mining using deep learning," in *2015 Fifth International Conference on Digital Information Processing and Communications (ICDIPC)*, 2015.
8. T. Erpek, T. J. O'Shea, Sagduyu, Y. Y. E., Shi, and C. Clancy, "Deep learning for wireless communications." <https://arxiv.org/abs/2005.06068>, 2020.
9. "AI, ML, and DL: How not to get them mixed!." <https://towardsdatascience.com/understanding-the-difference-between-ai-ml-and-dl-cceb63252a6c>, 2021 (accessed May 5, 2021).
10. R. E. Uhrig, "Introduction to artificial neural networks," in *Proceedings of 21st Annual Conference on IEEE Industrial Electronics*, 1995.
11. K. Hornik, M. Tinchcombe, and H. White, "Multilayer feedforward networks are universal approximators," *Neural Networks*, vol. 37, no. 2, pp. 359–366, 1989.
12. "Machine learning vs. deep learning: What's the difference?." <https://innovationatwork.ieee.org/machine-learning-vs-deep-learning-whats-the-difference/>, 2021 (accessed May 5, 2021).
13. I. Goodfellow, Y. Bengio, and A. Courville, *Deep Learning*. MIT Press, 2016.
14. N. O' Mahony, S. Campbell, A. Carvalho, S. Harapanahalli, G. Velasco-Hernandez, L. Krpalkova, D. Riordan, and J. Walsh, "Deep learning vs. traditional computer vision," in *Advances in Computer Vision Proceedings of the 2019 Computer Vision Conference (CVC)*, pp. 128–144, 2019.
15. P. Wlodarczak, J. Soar, and M. Ally, "Multimedia data mining using deep learning," in *2015 Fifth International Conference on Digital Information Processing and Communications (ICDIPC)*, 2015.
16. T. Erpek, T. J. O'Shea, Sagduyu, Y. Y. E., Shi, and C. Clancy, "Deep learning for wireless communications." <https://arxiv.org/abs/2005.06068>, 2020.

17. “AI, ML, and DL: How not to get them mixed!” <https://towardsdatascience.com/understanding-the-difference-between-ai-ml-and-dl-cceb63252a6c>, 2021 (accessed May 5, 2021).
18. R. E. Uhrig, “Introduction to artificial neural networks,” in Proceedings of 21st Annual Conference on IEEE Industrial Electronics, 1995.
19. K. Hornik, M. Tinchcombe, and H. White, “Multilayer feedforward networks are universal approximators,” *Neural Networks*, vol. 37, no. 2, pp. 359–366, 1989.
20. “Machine learning vs. deep learning: What’s the difference?.” <https://innovationatwork.ieee.org/machine-learning-vs-deep-learning-whats-the-difference/>, 2021 (accessed May 5, 2021).
21. I. Goodfellow, Y. Bengio, and A. Courville, *Deep Learning*. MIT Press, 2016.
22. E. Bjornson and P. Giselsson, “Two applications of deep learning in the physical layer of communications systems,” *IEEE Signal Processing Magazine*, vol. 37, no. 5, pp. 134–140, 2020.
23. Z. Qin, H. Ye, G. Y. Li, and B.-H. F. Juang, “Deep learning in physical layer communications,” *IEEE Wireless Communications*, vol. 26, no. 2, pp. 93–99, 2019.
24. T. O’Shea and J. Hoydis, “An introduction to deep learning for the physical layer,” *IEEE Transactions on Cognitive Communications and Networking*, vol. 3, no. 4, pp. 563–575, 2017.
25. T. O’Shea and J. Hoydis, “An introduction to machine learning communication systems.” <https://www.researchgate.net/publication/313365686>, 2017.